

DS-6 Switch, 24 Ports

The DS-6 Fast Ethernet Switch Module enables you to access all connected devices within the DS-6 system. It distributes all data.

The module is designed to be installed in 19 inch slot carrier with three height units according to DIN EN 60297-3-101 or IEC 60297-.



DS-6 Switch
Art.-No. 3 326 4

Equipment features

- Front plate contains 24 10/100 Mbit/s Ports
- Two green LEDs pro Port

Art.-No.	3 326 4
Physical data	
Dimensions (W x D x H)	280 x 180 x 44 mm
Weight	2,8 kg
Technical data	
Operating voltage	48V DC (24-60V)
Maximum power consumption	5 W
Supported standards	IEEE 802.3, 10BASE-T Ethernet IEEE 802.3u 100 BASE-TX Fast Ethernet ANSI/IEEE 802.3 NWay Auto-Negotiation IEEE 802.3x Flow Control
Network interface	RJ45 socket for 10BASE-T or 100BASE-TX-Ethernet interface
Data frame filter rate	max. 14.800 data frame for 10 Mbit/s-Port max. 148.800 data frame for 100 Mbit/s-Port
Date frame transmission rate	max. 14.800 data frame for 10 Mbit/s-Port max. 148.800 data frame for 100 Mbit/s-Port
Queue buffer	2,5 MB
Environmental data	
Admissible temperature range	+5°C ... +40°C