

Diagnostic PC Server 19"

The TIMM OPC Server provides an OPC interface for the integration into supervising management systems. In this way the communication between our systems and a SCADA system, for example can be established.

By means of the TIMM OPC Server, DS-6 devices can be controlled by the management system or send messages to be displayed at the management system.

By default, the software which is required for OPC controlling is installed on every TIMM OPC Server. Additionally, the TIMM Configuration OPC Software per line (Art.-No. 5 610 2) is required.

The TIMM OPC Server is an industrial computer that is specially designed for alarm and evacuation systems with high safety requirements. The industrial computer provides a high degree of reliability and system stability.

It is integrated in a 19" housing with, however, only one height unit and a small installation depth of 356 mm.



Exemplary Picture

Diagnostic PC Server 19"
Art.-No. 2 374 6

Equipment Features

- 1,6GHz CPU frequency, ATOM
- 2048MB DDR2 PC667 RAM
- VGA Controller integrated with Chipset (VGA, DVI, TV)
- Ethernet Channel, 10/100Mbps
- 4 x RS-232 Ports (2 x standard, 2 x 1kV isolated)
- 6 x USB 2.0
- Audio, Built-in Chipset
- 320 GB HDD

Art.-No.	2 374 6
Physical data	
Dimensions	Width: 19"; height: 1 HU
Installation depth	302 mm (housing without connectors)
Weight	approx. 4,5 kg
Device data	
Type of processor	Intel ATOM
RAM	≥ 2GB
Hard disk	≥ 320GB
Network interfaces	2 x LAN 10/100Mbps LAN (RJ-45)
Operating system	Windows
Power supply	
Operating nominal voltage	48V DC
Power consumption	300W
Environmental data	
Admissible temperature range	+5 ... +40°C
Protection class	IP20 in conformity with DIN EN 60529

Diagnostic PC Server 19" Software

Article	Art.-No.
MDK Service for remote maintenance and diagnostic	5 002 7

Assessories

Article	Art.-No.
Stabilizer for 19" devices	21 3 3209 049 3