

## ISDN Telephone Gateway

The ISDN Telephone Gateway is used for the integration of an ISDN PABX into the TIMM system. Therefore, there are different versions according to the application:

- 1xS0/2xAnalogue
- 2xS0
- 1xS2M

All required licences as well as the installation are inclusive. In addition, the configuration of the ISDN Telephone gateway per channel (Art.-No. 5 609 0) is required.

For mounting into a cabinet a 19" mounting frame with one high unit (Art.-No. 919 1116 716 2) is optional available.

### Exemplary Pictures



**ISDN Telephone Gateway  
1xS0/2xAnalogue**  
Art.-No. 3 377 0



**ISDN Telephone Gateway 2xS0**  
Art.-No. 3 378 1



**ISDN Telephone Gateway 1xE1**  
Art.-No. 3 379 2

Art.-No.	3 377 0	3 378 1	3 379 2
<b>Physical Data</b>			
Dimensions	210 x 134 x 32 mm	210 x 134 x 32 mm	210 x 184 x 32 mm
Weight	680 g	660 g	1050 g
<b>Technical data</b>			
Interfaces	2 x a/b 1 x S0 2 x Ethernet 10/100-BASE-TX (auto negotiation)	2 x S0 2 x Ethernet 10/100-BASE-TX (auto negotiation)	1 x E1 2 x Ethernet 10/100-BASE-TX (auto negotiation)
Power supply	Power over Ethernet acc. to 802.3af, Class 3 or power supply adapter primary: 100-240V, 50Hz, 200mA secondary: 40VDC, 12W	Power over Ethernet acc. to 802.3af, Class 3 or power supply adapter primary: 100-240V, 50Hz, 200mA secondary: 40VDC, 12W	Power over Ethernet acc. to 802.3af, Class 3
Operating temperature	0...+45°C	0...+45°C	0...+45°C
Storage temperature	-10...+70°C	-10...+70°C	-10...+70°C
Relative humidity	10...90 % (not condensing)	10...90 % (not condensing)	10...90 % (not condensing)

## ISDN Telephone Gateway Software

Article	Art.-No.
TIMM Configuration Analogue/ISDN-Gateway Software per Port/Channel	5 609 0