

## Indoor wall-mounted Loudspeakers 6W / 100V

The Wall-mounted Loudspeaker is equipped with a high-quality, full range loudspeaker and is distinguished by good music reproduction and clear speech intelligibility.

To mount the unit, the loudspeaker rear panel is first mounted to the wall with two screws. Afterwards, the housing is placed onto the panel and fastened with two sturdy springs.



### Wall-mounted Loudspeaker, 6 W / 100 V

Art.-No. 4 775 3  
(without volume control)

Art.-No. 4 776 4  
(with volume control)

#### Equipment features

- White wooden housing with perforated face plate
- Connection to the 100 V network
- Built-in volume control with spring terminals

Art.-No.	4 775 3 / 4 776 4
<b>Physical data</b>	
Dimensions (W x H x D)	280 x 170 x 65 mm
Weight	approx. 1,4 kg
Colour	white
Volume control	□ / ●
<b>Electrical data</b>	
Nominal output	6 W
Transformer matching (100 V)	6; 3; 1,5 W
Impedance	1,66; 3,33; 6,66 kΩ
Frequency range	150 Hz to 20 kHz
Average sound pressure (1 W / 1 m)	96 dB
max. sound pressure P <sub>max</sub> / 1 m	102 dB (6 W)